

ID-Nr. 36418-001 Model UB90.080.110.060.2T



Dimensions	
Width (external)	1102.00 mm
Depth (external)	600.00 mm
Height (external)	800.00 mm
Width (internal)	979.00 mm
Depth (internal)	482.00 mm
Height (internal)	702.00 mm
The available internal dimensions can vary depend	ding on the interior equipment package

The available internal dimensions can vary depending on the interior equipment package.

Neight / Load	
Weight without interior equipment	233 kg
Distributed load	302.00 kg/m ²
Maximum load	300 kg
entilation	
extraction air	50 DN
Ainimum exhaust air quantity 10 times	2 m³/h
Differential pressure (10 times air change)	1 Pa
Colouring / Surface finish	
Body colour code	RAL 7035
Body colour	light grey
Body surface finish	plain

Body surrace finish	piain
Door / Drawer colour code	RAL 7035
Door / Drawer colour	light grey
Door / Drawer surface finish	plain
General Information	
Number of doors	2
Door opening angle	07.000

1044 mm

94032080

Depth with open doors

Customs tariff number













safety storage under bench cabinet UB-T-90 Model UB90.080.110.060.2T, light grey (RAL 7035)

Safe and approved storage of flammable hazardous substances in working areas

Function / construction:

- Robust construction and longevity: body made of powdercoated sheet steel
- Easy handling with comfort: doors stop in any position, self-closing in the event of fire
- **User-friendly:** access to all containers, 93° opening of the wing door, interior of the cabinet completely visible
- **No unauthorised use:** doors lockable with cylinder lock and locking state indicator (red/green)
- Mobile: castors with plinth (optionally available), easy moving of the cabinet
- **Ventilation:** integrated air ducts ready for connection (DN 50) to a technical exhaust system

